

AMP MCP 2.8, AMP MCP Connector System

TE Internal #: 929092-1

Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 16

Position, .2 in [5.08 mm] Centerline, Black, Signal, Hybrid

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > AMP MCP, UNSEALED CONNECTOR HOUSING



Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 2.8 mm [.11 in]

Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 16

Centerline (Pitch): 5.08 mm [.2 in]

All AMP MCP, UNSEALED CONNECTOR HOUSING (187)

Features

Product Type Features

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board, Wire-to-Device
Sealable	No
Hybrid Connector	No
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	16
Number of Rows	4
Electrical Characteristics	

Operating Voltage	28 VDC
Nominal Voltage Architecture	12 V, 24 V

Body Features

Cable Exit Angle	Other
Body Material	PA
Primary Product Color	Black

Contact Features



Contact Size	2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mechanical Attachment	
Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	5.08 mm[.2 in]
Dimensions	
Product Width	23.5 mm[.925 in]
Product Length	28.4 mm[1.118 in]
Product Height	28.9 mm[1.138 in]
Row-to-Row Spacing	5.08 mm[.2 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operating Temperature Range Operation/Application	-40 - 120 °C[-40 - 248 °F]
	-40 – 120 °C[-40 – 248 °F] Signal
Operation/Application	
Operation/Application Circuit Application	
Operation/Application Circuit Application Industry Standards	Signal
Operation/Application Circuit Application Industry Standards UL Flammability Rating	Signal
Operation/Application Circuit Application Industry Standards UL Flammability Rating Packaging Features	Signal UL 94HB
Operation/Application Circuit Application Industry Standards UL Flammability Rating Packaging Features Packaging Quantity	Signal UL 94HB 1000
Operation/Application Circuit Application Industry Standards UL Flammability Rating Packaging Features Packaging Quantity Packaging Method	Signal UL 94HB 1000



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Not Yet Reviewed
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | AMP MCP 2.8



Automotive Connector Caps & Covers (1)



Automotive Connector Locks & Position Assurance(6)



Automotive Housings(179)



Automotive Seals & Cavity Plugs(1)





Automotive Terminals(6)



Insertion & Extraction Tools(6)



Module Components(1)




PCB Headers & Receptacles(1)

Also in the Series | AMP MCP Connector System



Automotive Connector Caps & Covers (24)



Automotive Connector Locks & Position Assurance(7)



Automotive Housings(352)



Automotive Seals & Cavity Plugs(6)



Automotive Terminals(125)



Insertion & Extraction Tools(13)



Other Automotive Connector Accessories(2)




PCB Headers & Receptacles(29)

Customers Also Bought




TE Part #4-1418448-1 3POS AMP MCP1.5 REC. HSG COD D



TE Part #965665-1 STD-POW-TIM GEH 2P



TE Part #1-968968-1 CIRCULAR DIN HOUSINGS



TE Part #927768-6 JPT REC 2.8 Contact SRC Ag



TE Part #1-1355849-1 AMP MCP 9.5, CONTACT, LANCELESS



TE Part #1-2840573-1
PCON12,TERMINAL,FAM SLD/UNSLD



TE Part #4-880490-2 FUSE CONTACT - BUS





Documents

Product Drawings

MCP2,8 GEH ASSY2X8P

English

CAD Files

Customer View Model

ENG_CVM_929092-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_929092-1_B.3d_stp.zip

English

Customer View Model

ENG_CVM_929092-1_B.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Product Specifications

Product Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English