






| REVISIONS | | | | | |
|-----------|-----|------------------------|---------|-------|-------|
| REV | ECO | DESCRIPTION | DATE | BY | APPR |
| A3 | - | RELEASE NEW DWG FORMAT | 11DEC13 | JARRY | |
| A4 | - | ADD COLOR "ORANGE" | 13MAR20 | VITO | TOMMY |
| A5 | - | UPDATE NOTE | 23NOV20 | LOUIE | TOMMY |



REQUIRES CONTACT RETENTION WEDGE AW3S



STANDARD COLOR IS GREY, ADDITION COLOR SHOWN IN PART NUMBER CHART



STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

NOTES: UNLESS OTHERWISE SPECIFIED

- MATERIAL:
HOUSING: THERMOPLASTIC
SEAL: SILICONE RUBBER
- MODIFICATIONS: END CAP
- SPECIFICATIONS:
 - CURRENT RATING: 13 AMPS
 - OPERATING TEMPERATURE: -55°C TO +125°C
 - DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - MOISTURE RESISTANCE:
IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION)
IP69K(MATED CONDITION)
 - MATING CYCLE DURABILITY: 100 CYCLES
 - RoHS COMPLIANT
- MATING PART: AT04-3P* RECEPTACLE
(* = MODIFICATIONS AND COLORS)
- ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND REAR SEAL WIRE RANGE:

| CONTACT SIZE | MIN. INSUL O.D. | MAX. INSUL O.D. | TYPICAL WIRE RANGE |
|--------------|----------------------|----------------------|--|
| 16 | 2.24 mm (.088 in) | 3.68 mm (.145 in) | 14 - 20 AWG (2.0-0.5mm ²) |

| PART NUMBER CHART | |
|-------------------|-----------------|
| COLOR | PART NUMBER |
| GREY | AT06-3S-EC01 |
| BLACK | AT06-3S-EC01BLK |
| BLUE | AT06-3S-EC01BLU |
| BROWN | AT06-3S-EC01BRN |
| GREEN | AT06-3S-EC01GRN |
| RED | AT06-3S-EC01RED |
| WHITE | AT06-3S-EC01WHT |
| YELLOW | AT06-3S-EC01YEL |
| ORANGE | AT06-3S-EC01ORG |

| SEE PART NUMBER CHART | | REF: DT06-3S-E003, DT06-3S-E005, DT06-3S-EP04, DT06-3S-EP06 | |
|--|--|--|--|
| PART NUMBER | | DESCRIPTION | |
| QUANTITY | | ITEM | |
| MATERIALS LIST UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.16 3 PL DEC ±0.06 Fractions ±1/64 Angles ±1° 3) Note reference = | | | |
| SIGNATURES | | DATE | |
| DRAWN: LOUIE | | 23NOV20 | |
| CHECKED: ORION | | 25NOV20 | |
| ENGINEER: | | | |
| APPROVAL: TOMMY | | 27NOV20 | |
| CUSTOMER: | | | |
| MATERIAL SPECIFICATIONS: | | | |
| PROCESS SPECIFICATIONS: | | THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. | |
| NEXT ASSY: | | | |
| SIZE B C- | | DWG NO: AT06-3S-EC01XXX | |
| SCALE: NONE | | REVISION A5 | |
| | | SHEET 1 OF 1 | |

TITLE:

PLUG 3 SOCKET, AT SERIES, END CAP

DWG NO:

AT06-3S-EC01XXX

REV: A5

SH: 1

OF: 1