

MATE-N-LOK | 0.140 MATE-N-LOK

TE Internal #: 925866-2

Connector Contacts, Socket, Pre-Tin, Silver, 250 VAC, Locking

Lance Contact Retention, Wire-to-Wire, Discrete Wire, 0.140 MATE-

N-LOK

View on TE.com >



Connectors > Rectangular Connectors > Connector Contacts











Contact Type: Socket

Contact Mating Area Plating Material: Pre-Tin

Wire Contact Termination Area Plating Material: Silver

Operating Voltage: 250 VAC

Contact Retention Within Housing: With

Features

Product Type Features

Froduct Type Features	
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire
Electrical Characteristics	
Operating Voltage	250 VAC
Contact Features	
Contact Diameter	3.56 mm[.14 in]
Contact Length	20 mm[.787 in]
Contact Type	Socket
Contact Mating Area Plating Material	Pre-Tin
Wire Contact Termination Area Plating Material	Silver
Contact Retention Within Housing	With
Contact Base Material	Copper Tin



Contact Current Rating (Max)	28 A
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Contact Retention Type Within Housing	Locking Lance
Connector Mounting Type	Cable Mount (Free-Hanging)
Dimensions	
Accepts Wire Insulation Diameter Range	2.5 – 4.5 mm[.098 – .177 in]
Wire Size	$.5 - 2.1 \text{ mm}^2$
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Packaging Features	
Packaging Method	Box
Packaging Quantity	500
Other	
Comment	Without Locking Lance

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-480585-0 09P .140 MNL PLUG NAT



TE Part # 1-350346-0 03P .140 MNL PLUG P/M NAT



TE Part # 1-480672-0 09P .140 MNL PLUG PM NAT





TE Part # 1-480510-0 04P .140 MNL PLUG NAT



TE Part # 539764-1
EXTRACTION TOOL



TE Part # 880124 9 CIR PLUG 140DIA PANEL MT NAT



TE Part # 925451-1 M-N-L SOCKET HSG




TE Part # 1-480672-9 09P .140 MNL PLUG PM BLK




Also in the Series | 0.140 MATE-N-LOK











Insertion & Extraction Tools(1)


Power Contacts(9)

Rectangular Power Connectors(1)

Customers Also Bought













Documents

Product Drawings

.140 DIA SOCKET

English

.140 DIA SOCKET

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_925866-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_925866-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_925866-2_A.3d_stp.zip

Connector Contacts, Socket, Pre-Tin, Silver, 250 VAC, Locking Lance Contact Retention, Wire-to-Wire, Discrete Wire, 0.140 MATE-N-LOK



English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English