SPLICE

TE Internal #: 963920-1

Splices, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Splice

Capacity 2, 400 – 1000 CMA Wire Size, Copper Alloy, Pigtail Splice

Splice, SPLICE

View on TE.com >



Terminals & Splices > Splices











Wire Size: .2 – .6 mm²

Sealable: No

Splice Capacity: 2

Accepts Wire Insulation Diameter Range: 1.6 mm [.062 in]

Features

Product Type Features

Barrel Style	Standard
Sealable	No
Splice Type	Pigtail Splice
Serrated	Yes
Wire Insulation Support Retention Type	Insulation Support

Configuration Features

Strip Orientation	End Feed
Splice Capacity	2
Number of Serrations	4
Compatible With Wire & Cable Type	Discrete Wire

Electrical Characteristics

Operating Voltage	250 V	

Body Features

Weight per Piece	.158 g	



Plating Material	Pre-Tin
Primary Product Material	Copper Alloy
Contact Features	
Contact Plating Material	Pre-Tin
Barrel Type	Open
Termination Features	
Termination Method	Crimp
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	400 – 1000 CMA
Accepts Wire Insulation Diameter Range	1.6 mm[.062 in]
Terminal Material Thickness	.33 mm[.013 in]
Overall Product Length	14.3 mm[.563 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-65 – 150 °C[-85 – 302 °F]
Operation/Application	
Heavy Duty	No
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	5000
Packaging Method	Strip

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224)



Candidate List Declared Against: JAN 2022

(223)

SVHC > Threshold:

Not Yet Reviewed

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Also in the Series | SPLICE









TE Part #2-2141047-5 6POS MIXED MQS REC COD B





TE Part #AS014-35PD
RECEPT 2 HOLE MTG.TYPE 0





TE Part #ASDD014-64SB

RECEPT 2 HOLE MTG ASSY 14-64 AS

DOUBLE D



TE Part #ASU103-03PA-HE
RECEPT ASSY INLINE AS 3 WAY



TE Part #2208339-3 TE Part #8-10POS,NANOMQS,REC HSG,COD C EXTRACTION

EXTRACTION

EXTRACTION

TE Part #8-10POS,NANOMQS,REC HSG,COD C



TE Part #968074-3 MPQ,TERMINAL,2.8 AGRECLL UNSEAL. 0,5-1,0

Documents

Product Drawings

BUTT SPLICE LP 0.2-0.5 MM2 PTP CUSN4

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_963920-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_963920-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_963920-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Splices, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Splice Capacity 2, 400 – 1000 CMA Wire Size, Copper Alloy, Pigtail Splice Splice, SPLICE



Product Specification

English