

AMP | MQS

TE Internal #: 929682-3

Housing for Female Terminals, Wire-to-Device / Wire-to-Board, 12 Position, .1 in [2.54 mm] Centerline, Black, Signal, Cable Mount

(Free-Hanging), MQS

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > MQS, CONNECTOR HOUSING



Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: .63 mm [.025 in]

Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 12

Centerline (Pitch): 2.54 mm [.1 in]

All MQS, CONNECTOR HOUSING (557)

Features

Product Type Features

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board, Wire-to-Device
Sealable	No
Hybrid Connector	No
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	12
Number of Rows	2
Electrical Characteristics	
Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V
Body Features	
Cable Exit Angle	180°
Body Material	PBT GF

Black

Primary Product Color



Contact Features

Contact Size	.63mm
Contact Type	Receptacle
Mating Tab Width	.63 mm[.025 in]

Mechanical Attachment

Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
--------------------	----------------

Dimensions

Product Width	16 mm[.63 in]
Product Length	19.4 mm[.764 in]
Product Height	7.1 mm[.28 in]
Row-to-Row Spacing	2.54 mm[.1 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F]
Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]

Operation/Application

Circuit Application	Signal	
Industry Standards		

OL Hammability Nating	UL Flammability Rating	UL 94HB	
-----------------------	------------------------	---------	--

Packaging Features

Packaging Method	Carton	
------------------	--------	--

Other

Serviceable	No	
Serviceable	140	
Connector Position Assurance Capable	No	



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series MQS






Automotive Connector Caps & Covers (132)



Automotive Connector EMC Shielding (2)



Automotive Connector Locks & Position Assurance(29)



Automotive Housings(489)



Automotive Seals & Cavity Plugs(26)




Automotive Terminals(96)



Insertion & Extraction Tools(42)



Other Automotive Connector Accessories(13)



PCB Headers & Receptacles(207)

Customers Also Bought



TE Part #1-1355880-1 AMP MCP 2.8, CONTACT LANCELESS



TE Part #6-1355688-5 MT3-REC. HOUSING, 10 POS.



TE Part #1-2209521-1 46POS. COVER ASSY



TE Part #2066561-1
MOUNTING BRACKET, ENGINE
COMPT FRB

TE Part #2208343-3 TERMINAL, 6,3MM

TE Part #2066594-1

TYPE A FUSE MODULE, 14P, ASSY

TE Part #2066596-1
MICRO RELAY MODULE, 4P, ASSY

TE Part #2066602-1 MINIATURE FUSE MODULE, 16P, ASSY



TE Part #2298631-1 48POS,HYBRID,TAB HSG ASSY, UNSLD,COD A TE Part #2316763-1 48POS,HYBRID,REC HSG ASSY, UNSLD,COD A

Documents

Product Drawings

MQS BU-GEH 2X6P

English

CAD Files

Customer View Model

ENG_CVM_929682-3_C3.3d_igs.zip

English

Customer View Model

ENG_CVM_929682-3_C3.3d_stp.zip

English

Customer View Model

ENG_CVM_929682-3_C3.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

Micro Quadlok Interconnection System (MQS)

English

Product Specifications

Application Specification

English