

926820-3 ✓ ACTIVE

[Positive Lock](#) | [Positive Lock 250](#)

TE Internal #: 926820-3

Quick Disconnects, Receptacle, 20 – 15 AWG Wire Size, .51 – 1.65 mm² Wire Size, Mating Tab Width .25 in [6.35 mm], Flag, Positive Lock 250

[View on TE.com >](#)



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: .51 – 1.65 mm²

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features

| | |
|-----------------|--------------|
| Terminates To | Wire & Cable |
| Wire/Cable Type | Regular Wire |
| Insertion Force | Low |
| Sealable | No |

Configuration Features

| | |
|---------------------|--------|
| Connection Capacity | Single |
|---------------------|--------|

Contact Features

| | |
|--------------------------------|------------------|
| Quick Disconnect Terminal Type | Receptacle |
| Mating Tab Width | 6.35 mm [.25 in] |
| Mating Tab Thickness | .81 mm [.032 in] |
| Terminal Orientation | Flag |
| Contact Base Material | Phosphor Bronze |
| Terminal Plating Material | Tin |
| Crimp Type | F-Crimp |
| Barrel Type | Open |



Mechanical Attachment

| | |
|-------------------------|------|
| Wire Insulation Support | With |
|-------------------------|------|

Dimensions

| | |
|--|-------------------------------|
| Accepts Wire Insulation Diameter Range | 2.2 – 3.1 mm [.086 – .122 in] |
| Receptacle Terminal Stock Thickness | .41 mm [.016 in] |
| Wire Size | .51 – 1.65 mm ² |

Usage Conditions

| | |
|-----------------------------|-----------------------------|
| Insulation Option | Uninsulated |
| Operating Temperature Range | -40 – 110 °C [-40 – 230 °F] |

Packaging Features

| | |
|--------------------|------------|
| Packaging Quantity | 2000 |
| Packaging Method | Strip/Reel |

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

| | |
|---|---|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2-2150401-1
OCEAN_2.0_Applicator-E-100F140F



TE Part # 2-2150401-2
OCEAN_2.0_Applicator-E-100F140F



TE Part # 2-2150908-1
OCEAN-2.0-APPLICATOR-E-100F120OV



TE Part # 2-2150908-2
OCEAN-2.0-APPLICATOR-E-100F120OV



TE Part # 2150401-1
OCEAN_2.0_Applicator-E-100F140F



TE Part # 2150401-2
OCEAN_2.0_Applicator-E-100F140F



TE Part # 2150908-1
OCEAN-2.0-APPLICATOR-E-100F120OV



TE Part # 2150908-2
OCEAN-2.0-APPLICATOR-E-100F120OV



TE Part # 680436-1
HDM 9EMPO100F120F T&G



TE Part # 7-2150401-1
OCEAN_2.0_Applicator-E-100F140F



TE Part # 7-2150401-2
OCEAN_2.0_Applicator-E-100F140F




TE Part # 7-2150401-7
OCEAN_2.0_SPARE_PART_KIT-100F140F




TE Part # 7-2150908-7
OCEAN_2.0_SPARE_PART_KIT-100F120OV

Also in the Series | **Positive Lock 250**



Automotive Terminals(1)



Crimp Terminal Housings(203)



Insertion & Extraction Tools(3)




Insulation Boots & Sleeves(4)



Quick Disconnects(189)


Customers Also Bought



TE Part #6-2208800-6
53POS MIXED MQS REC SEALED
COD 1




TE Part #1563200-1
COVER,90,53 WAY PCM CONN




TE Part #1-1924337-3
Shield Assy, 54 POSN, 0.64mm, 20
DEG BLK




TE Part #9-2208798-5
6POS,0.64 GENER. Y,REC HSG,ASSY



TE Part #1438521-1
FEMALE ASSEMBLY, 60 WAY, GET,
TCM CONN




TE Part #2050786-3
Ford T6 Body Passenger Seatbelt
Cable




TE Part #2050786-4
Ford T6 Body Driver Seatbelt Cable



TE Part #2098811-1
38 Way ABS Connector Wire Dress
Cover



TE Part #2208798-6
6POS,0.64 GENER. Y,REC HSG,ASSY



TE Part #2272223-2
38 WAY ABS CONNECTOR ASSY KEY
LEFT EXIT

Documents



Product Drawings

POS-LOCK FAH-STECKH

English

CAD Files

Customer View Model

[ENG_CVM_CVM_926820-3_G.2d_dxf.zip](#)

English

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_926820-3_G.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_926820-3_G.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[1654742_HOUSEHOLD_APPLIANCES_RAST5](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[TE Material Declaration](#)

English
