DT4P-BT-BK - ACTIVE

TE Internal #: DT4P-BT-BK Automotive Connector Caps & Covers, Boot, Cable Exit Angle 180° (In-Line), Black, PVC, Wire-to-Wire, 4 Position, -20 – 212 °F [-29 – 100 °C]

View on TE.com >



Connectors > Automotive Connectors > Connector Accessories > Connector Caps & Covers



Protection & Strain Relief Accessory Type: Boot

Cable Exit Angle: 180° (In-Line)

Strain Relief: With

Primary Product Color: Black

Primary Product Material: PVC

Features

Product Type Features

Protection & Strain Relief Accessory Type	Boot
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	4
Body Features	
Cable Exit Angle	180° (In-Line)
Primary Product Color	Black
Primary Product Material	PVC
Mechanical Attachment	
Strain Relief	With
Dimensions	
Compatible Cable Bundle Diameter Range	0 – 10.82 mm[0 – .426 in]

DT4P-BT-BK

Automotive Connector Caps & Covers, Boot, Cable Exit Angle 180° (In-Line), Black, PVC, Wire-to-Wire, 4 Position, -20 – 212 °F [-29 – 100 °C]



Usage Conditions

Compatible With Connector Style	Receptacle
Operating Temperature (Max)	100 °C[212 °F]
Operating Temperature Range	-29 – 100 °C[-20 – 212 °F]
Industry Standards	
Degree of Protection	IP6K9K
Packaging Features	
Packaging Method	Box
Other	
Serviceable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022

(224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Not reviewed for solder process capability

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

DT4P-BT-BK

Automotive Connector Caps & Covers, Boot, Cable Exit Angle 180° (In-Line), Black, PVC, Wire-to-Wire, 4 Position, -20 – 212 °F [-29 – 100 °C]



Compatible Parts



Customers Also Bought



TE Part #DT4S-BT-BK	TE Part #DT2P-BT-BK	TE Part #DT2S-BT-BK	TE Part #DT6P-BT-BK
BOOT, 4P, PLG, ST, BLK	BOOT, 2P, REC, ST, BLK	BOOT, 2P, PLG, ST, BLK	BOOT, 6P, REC, ST, BLK



TE Part #9-927742-3 FASTIN FASTON HOUSING 3POS

Documents

Product Drawings BOOT, 4P, REC, ST, BLK

English

CAD Files

3D PDF

3D

DT4P-BT-BK

Automotive Connector Caps & Covers, Boot, Cable Exit Angle 180° (In-Line), Black, PVC, Wire-to-Wire, 4 Position, -20 – 212 °F [-29 – 100 °C]



Customer View Model

ENG_CVM_CVM_DT4P-BT-BK_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DT4P-BT-BK_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DT4P-BT-BK_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages CONNECTOR SELECTOR

English

Product Specifications Application Specification

English