# DRC16-70SB-P013 ✓ ACTIVE

## DEUTSCH | DEUTSCH DRC

TE Internal #: DRC16-70SB-P013

Housing for Female Terminals, Wire-to-Wire, 70 Position, .216 in [5.49 mm] Centerline, Sealable, Black, Wire & Cable, Power &

Signal, DEUTSCH DRC

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > DEUTSCH DRC HOUSINGS



Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 1.59 mm [.063 in]

Connector System: Wire-to-Wire

Number of Positions: 70

Centerline (Pitch): 5.49 mm [.216 in]

## All DEUTSCH DRC HOUSINGS (112)

## **Features**

## **Product Type Features**

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Contact Retainer
Connector & Contact Terminates To	Wire & Cable

## **Configuration Features**

Blank Cavity Position	0
Connector Modification	Bonded Front Seal
Number of Positions	70
Number of Rows	5

#### **Electrical Characteristics**

Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V

## **Body Features**

Cable Exit Angle	180°
Cable Exit Angle	100



Body Material	PPS GF
Primary Product Color	Black
Connector Code	В
Contact Features	
Contact Size	Size 16
Contact Type	Socket
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
Mounting Feature	Without
Terminal Position Assurance	No
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	5.49 mm[.216 in]
Dimensions	
Product Width	103.99 mm[4.094 in]
Product Length	41.73 mm[1.643 in]
Product Height	36.06 mm[1.421 in]
Row-to-Row Spacing	5.49 mm[.216 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Agency/Standard	SAE J2030
Degree of Protection	IP68, IP6K9K
UL Flammability Rating	20mm Flame Test per Standard UL-94



## **Packaging Features**

Packaging Quantity	50
Packaging Method	Box

#### Other

Serviceable	Yes
Connector Position Assurance Capable	No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not reviewed for solder process capability

## Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





TE Part # CAT-D799-CH8172 DEUTSCH DRC HOUSINGS



TE Part # CAT-D48-SP729 DEUTSCH SEALING PLUGS



TE Part # 0411-291-1405 EXT TOOL, SIZE 16, 14-16 AWG, N, GRN



TE Part # 0411-204-1605 EXT TOOL, SIZE 16, 16-18 AWG, N, DRK BLU



TE Part # CAT-D799-H342 DEUTSCH DRC HEADERS



TE Part # CAT-D48-SFT273 DEUTSCH STAMPED & FORMED CONTACTS



TE Part # CAT-D48-ST273 DEUTSCH SOLID CONTACTS



TE Part # CAT-D799-B128 DEUTSCH DRC BACKSHELLS



TE Part # DRC70-BT BOOT, 70P, 16SZ, PLG/REC, ST, BLK

TE Part # 0515-006-7005 PROTECT CVR, 70P, PLG, WHT, DRC16 TE Part # 0515-031-7005 WIRE ROUTER, 70P, BLK, PLG

# Also in the Series | DEUTSCH DRC



Automotive Connector Caps & Covers



Automotive Housings(112)



Insertion & Extraction Tools(7)



PCB Headers & Receptacles(41)

# Customers Also Bought



CLIP, STEEL, ZINC, 11MM HOLE, SIDE



TE Part #DRC16-70SA-P013 **DEUTSCH DRC HOUSINGS** 







## **Documents**

## **Product Drawings**

PLG, 70P, BLK, N, SEAL BOND, B

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DRC16-70SB-P013\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DRC16-70SB-P013\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DRC16-70SB-P013\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

## **Product Specifications**

**Application Specification** 

English

## Agency Approvals

**UL Report** 

English