

DEUTSCH | DEUTSCH DT

TE Internal #: DT04-3P-LE08

Housing for Male Terminals, Wire-to-Wire, 3 Position, .394 in [10.01 mm] Centerline, Sealable, Gray, Wire & Cable, Power & Signal,

DEUTSCH DT

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > DEUTSCH DT Series Housings & Connectors



Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 1.59 mm [.063 in]

Connector System: Wire-to-Wire

Number of Positions: 3

Centerline (Pitch): 10.01 mm [.394 in]

All DEUTSCH DT Series Housings & Connectors (461)

Features

Product Type Features

Connector & Housing Shape	Triangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Blank Cavity Position	0
Connector Modification	Welded Flange, Shrink Boot Adapter
Number of Positions	3

Electrical Characteristics

Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V

Body Features

Cable Exit Angle	180°
Body Material	PA GF



Primary Product Color	Gray
Contact Features	
Contact Size	Size 16
Contact Type	Pin
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
Mounting Feature	With
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	10.01 mm[.394 in]
Dimensions	
Product Width	40.51 mm[1.595 in]
Product Length	55.4 mm[2.181 in]
Product Height	31.75 mm[1.25 in]
Accepts Wire Insulation Diameter Range	2.23 – 3.68 mm[.088 – .145 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Agency/Standard	SAE J2030
Degree of Protection	IP68, IP6K9K
UL Flammability Rating	12mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	300



Packaging Method	Вох
r doraging modifical	Ben

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













TE Part # DT3P-DC PROTECT CVR, 3P, REC, GRY, DT



TE Part # CAT-D487-W416 DEUTSCH DT WEDGELOCKS




TE Part # CAT-D48-SFT273 DEUTSCH STAMPED & FORMED CONTACTS

TE Part # DT3P-L012-GKT GASKET, 3P, BLK, DT/DTM

Also in the Series | DEUTSCH DT



Automotive Connector Caps & Covers



Automotive Connector Locks & Position Assurance(73)



Automotive Housings(619)



Automotive Seals & Cavity Plugs(4)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(14)



PCB Headers & Receptacles(106)

Customers Also Bought



TE Part #2278730-1 3P CAN CONNECTOR, RECEPTACLE



TE Part #K1060045 Relay 30-314-12



TE Part #1534968-2 BOLT M5 WITH SQUARE HEAD



TE Part #1-966658-1 32pos MQS .63 header 180deg



TE Part #185403-1 MODULAR RELAY HOLDER



TE Part #2141033-1 COVER, FOR PRE FUSE MODULE



TE Part #881572-2 BUSBAR, STAMPED, CUSN4, 0.4 MM, 3 **POSN**

TE Part #1-21002-7 SCREW,CAP,SOCKET,BUTTON HEAD







Documents

Product Drawings

REC, 3P, GRY, N, XCAP, FLANGE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DT04-3P-LE08_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DT04-3P-LE08_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DT04-3P-LE08_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Agency Approvals

UL Report

Housing for Male Terminals, Wire-to-Wire, 3 Position, .394 in [10.01 mm] Centerline, Sealable, Gray, Wire & Cable, Power & Signal, DEUTSCH DT



English