# DTM04-3P-E004 ✓ ACTIVE

### DEUTSCH | DEUTSCH DT, DEUTSCH DTM

TE Internal #: DTM04-3P-E004

Housing for Male Terminals, Wire-to-Wire, 3 Position, .165 in [4.19 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal,

Hybrid

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > DEUTSCH DTM HOUSINGS



Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 1.02 mm [ .04 in ]

Connector System: Wire-to-Wire

Number of Positions: 3

Centerline (Pitch): 4.19 mm [.165 in]

### All DEUTSCH DTM HOUSINGS (95)

### **Features**

### **Product Type Features**

Product Type reatures	
Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Blank Cavity Position	0
Number of Positions	3
Number of Rows	1
Electrical Characteristics	
Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V
Body Features	
Cable Exit Angle	180°

PA GF

**Body Material** 



Primary Product Color	Black
Contact Features	
Contact Size	Size 20
Contact Type	Pin
Mating Pin Diameter	1.02 mm[.04 in]
Contact Current Rating (Max)	7.5 A
Mechanical Attachment	
Mounting Feature	With
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	4.19 mm[.165 in]
Dimensions	
Product Width	20.73 mm[.816 in]
Product Length	41.15 mm[1.62 in]
Product Height	16.21 mm[.638 in]
Accepts Wire Insulation Diameter Range	1.35 – 3.05 mm[.053 – .12 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Agency/Standard	SAE J2030
Degree of Protection	IP68, IP6K9K
UL Flammability Rating	20mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	1000



Packaging Method Box

#### Other

Serviceable	Yes
Connector Position Assurance Capable	No

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts


























## Also in the Series | DEUTSCH DT







Automotive Connector Locks & Position Assurance(73)



Automotive Housings(619)




Automotive Seals & Cavity Plugs(4)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(14)




PCB Headers & Receptacles(106)

Also in the Series | DEUTSCH DTM





Automotive Connector Caps & Covers (34)



Automotive Connector Locks & Position Assurance(17)



Automotive Housings(98)



Insertion & Extraction Tools(2)



## Customers Also Bought



TE Part #DTM04-4P-E004
DEUTSCH DTM HOUSINGS



TE Part #2203701-1 2POS, MCON 1.2 CB TAB 2p TL UNSEALED



TE Part #WM-3P WEDGE LOCK, 3P, REC, ORG, DTM



TE Part #7-1452665-2 MCON 1.2 LL REC SWS AU



TE Part #964265-3
TAB A 1.6x0.6 CONTACT CS SRC Au



TE Part #7-2266118-7 OCEAN\_2.0\_SPARE\_PART\_KIT-069F080O

TE Part #D513X-A2586X-010PD
PRESS XDCR D513X-A2586X-010PD

TE Part #GASMD210KF375HT RSEN-SMD DEVICE

TE Part #U5134-A29974-006BA
PRESS XDCR U5134-A29974-006BA

### **Documents**

Housing for Male Terminals, Wire-to-Wire, 3 Position, .165 in [4.19 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal, Hybrid



### **Product Drawings**

REC, 3P, BLK, N

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_DTM04-3P-E004\_99.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DTM04-3P-E004\_99.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DTM04-3P-E004\_99.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

**CONNECTOR SELECTOR** 

English

### **Product Specifications**

**Application Specification** 

English

### Product Environmental Compliance

**Product Compliance** 

English

**Product Compliance** 

English

### Agency Approvals

**UL Report** 

English