


Start > Search=DTB50GMFH* > DTB50GMFH

DTB50GMFH

DTB50GMFH : 50 Way Panel-Through Male housing



Assistant Add to Favorites

Email Datasheet Print Datasheet

FCI Brings You More

Contact our sales/technical support

Sample request

Price request

Customer Drawing

Specifications Mating Half

- Direct Link**
- Cross reference
 - RoHS/LF P/N Search
 - Customer drawing search
 - 3D model search
 - Application tooling
- Services**
- Contact us
 - Distributor list
 - Price request
 - Order samples
- Documentation**
- Free search
 - Search by category

General	Mechanical	Physical	Terminal 1 Type	Environmental	Other Features
General					
Application	Panel-Through				
Ways	50				
Product Type	Housing				
Coding	No				
Features	Particularly suitable for door connection Pre-assembled front grids support blade terminal guiding and mating Terminal position assurance (T.P.A.) - Locking cam Sealed protection IP 64 when equipped with a rubber boot Sealed version available with rear mat-seal High density connector using 1,5 mm and 2.8 mm Terminals				
Hybrid	No				
Main Terminal family	SICMA				
Main Terminal size	1.5 mm				
Sealed	Yes				
Terminal Size	1.5				
Mechanical					
Connector mating force	< 90N				
Physical					
Color	Black				
Material	PBT				
Temperature (Range)	-40°C to +125°C				
Terminal 1 Type					
Terminal type 1	SICMA Female 1.5 mm Terminal				
Ways for Terminal Type 1	50				
Contact insertion force for Terminal Type 1	< 10N				
Retention force (Contact) for Terminal Type 1	> 80N				
Environmental					
IMDS	Yes				
Other Features					
Market	Passenger Vehicles				
Type	Female				
Part Situation	Active				
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.				