# DTM06-4S-E003 ✓ ACTIVE

#### DEUTSCH | DEUTSCH DT, DEUTSCH DTM

TE Internal #: 2298287-1

Housing for Female Terminals, Wire-to-Wire, 4 Position, .165 in [4.19 mm] Centerline, Sealable, Gray, Wire & Cable, Power &

Signal, Hybrid

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > DEUTSCH DTM HOUSINGS











Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 1.02 mm [ .04 in ]

Connector System: Wire-to-Wire

Number of Positions: 4

Centerline (Pitch): 4.19 mm [ .165 in ]

All DEUTSCH DTM HOUSINGS (95)

### **Features**

#### **Product Type Features**

**Electrical Characteristics** 

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Blank Cavity Position	0
Number of Positions	4
Number of Rows	2



Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V
Body Features	
Cable Exit Angle	180°
Body Material	PA GF
Primary Product Color	Gray
Contact Features	
Contact Size	Size 20
Contact Type	Socket
Mating Pin Diameter	1.02 mm[.04 in]
Contact Current Rating (Max)	7.5 A
Mechanical Attachment	
Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Polarization Slot
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	4.19 mm[.165 in]
Dimensions	
Product Width	17.63 mm[.694 in]
Product Length	31.37 mm[1.235 in]
Product Height	17.65 mm[.685 in]
Row-to-Row Spacing	7.11 mm[.28 in]
Accepts Wire Insulation Diameter Range	1.35 – 3.05 mm[.053 – .12 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
In alcostant Chamalanda	



Agency/Standard	SAE J2030
Degree of Protection	IP68, IP6K9K
UL Flammability Rating	20mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	1600
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





TE Part # CAT-D485-CH8172 DEUTSCH DTM HOUSINGS



TE Part # WM-4S WEDGE LOCK, 4P, PLG, ORG, DTM



=TE TE Part # CAT-D48-SP729 EXT TOOL, FRONT RELEASE DEUTSCH SEALING PLUGS





# Also in the Series | DEUTSCH DT





Position Assurance(73)





Automotive Seals & Cavity Plugs(4)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(14)



PCB Headers & Receptacles(106)

Also in the Series | DEUTSCH DTM





Automotive Connector Caps & Covers (34)



Automotive Connector Locks & Position Assurance(17)



Automotive Housings (98)





# Customers Also Bought



TE Part #WM-6P WEDGE LOCK, 6P, REC, ORG, DTM



TE Part #1703810-6 SLIDE,TAB HSG GROUP B



TE Part #DT04-6P-EP14

DEUTSCH DT Series Housings &

Connectors











### **Documents**

**Product Drawings** 

DTM06-4S-E003, PLG, 4P, GRY, N, CAP

English

**CAD Files** 

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_2298287-1\_A.2d\_dxf.zip

Housing for Female Terminals, Wire-to-Wire, 4 Position, .165 in [4.19 mm] Centerline, Sealable, Gray, Wire & Cable, Power & Signal, Hybrid



English

**Customer View Model** 

ENG\_CVM\_CVM\_2298287-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2298287-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

**Product Specifications** 

**Application Specification** 

English

**Agency Approvals** 

**UL Report** 

English