

DEUTSCH | DEUTSCH DT

TE Internal #: DT15-6P

PCB Mount Header, Vertical, Wire-to-Board, 6 Position, .175 in [1.45 mm] Centerline, Fully Shrouded, Nickel (Ni), Through Hole - Solder,

DEUTSCH DT

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > DEUTSCH DT HEADERS



Connector System: Wire-to-Board

Number of Positions: 6

Centerline (Pitch): 1.45 mm [.175 in]

Sealable: Yes

PCB Mount Orientation: Vertical

All DEUTSCH DT HEADERS (69)

Features

Product Type Features

Product Type reatures	
Hybrid Header	No
Connector & Housing Shape	Rectangular
PCB Connector Assembly Type	PCB Mount Header
Header Type	Fully Shrouded
Connector System	Wire-to-Board
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Sections	1
Number of Signal Positions	6
Number of Positions	6
PCB Mount Orientation	Vertical
Number of Rows	2
Electrical Characteristics	
Voltage Rating (Max)	250 VAC
Nominal Voltage Architecture	12 V, 24 V

250 VAC

Operating Voltage



Body Features

body realures	
Primary Product Color	Gray
Contact Features	
Contact Size	Size 16
Contact Type	Pin
Mating Pin Diameter	1.59 mm[.063 in]
Contact Mating Area Plating Material	Nickel (Ni)
Contact Current Rating (Max)	13 A
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mounting Holes	With
Mating Alignment Type	Not Keyed
Mating Retention	With
Mating Alignment	Without
PCB Mount Alignment	Without
Panel Mount Feature	With
PCB Mount Retention	With
PCB Mount Retention Type	Mounting Screw
Mating Retention Type	Locking Interface
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	1.45 mm[.175 in]
Dimensions	
Connector Length	39.5 mm[1.555 in]
Connector Width	42.8 mm[1.685 in]
PCB Thickness (Recommended)	.78 – 2.36 mm[.031 – .093 in]
Profile Height from PCB	35.26 mm[1.388 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application



Shielded	No
Circuit Application	Power & Signal
Industry Standards	
Degree of Protection	Not Tested
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Features Packaging Type	Box
	Box 210
Packaging Type	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | DEUTSCH DT



Automotive Connector Caps & Covers



Automotive Connector Locks & Position Assurance(73)



Automotive Housings(619)




Automotive Seals & Cavity Plugs(4)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(14)




PCB Headers & Receptacles(106)


Customers Also Bought



TE Part #2299804-3 NRW NON-FABRIC BOLSTER,P0, W /O COVER



TE Part #5177985-5 0.8FH,R05H.5,120,08/Sn,TR,SC



TE Part #3-1623788-2 SQM5 56R 5% (WIRE)



TE Part #1551576-5 Shield Finger, 3.4mm



TE Part #DTF13-3P
DEUTSCH DT HEADERS



TE Part #DTMH04-3PA REC, 3P, BLK, N, HI TEMP, A



TE Part #1-174954-1 070 MLC CAP ASSY V 6P



TE Part #DRC20-50P05 HDR, 50P, BLK, ST, AU/NI/CU, 05



Documents

Product Drawings

HDR, 6P, GRY, ST, NI/CU

English

CAD Files

Customer View Model

ENG_CVM_CVM_DT15-6P_99.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DT15-6P_99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DT15-6P_99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_DT15-6P_03222018522_dmtec

English

MD_DT15-6P_03222018522_dmtec

English

Agency Approvals

UL Report

English