# DT04-12PB-LE21 ACTIVE

#### DEUTSCH | DEUTSCH DT

TE Internal #: DT04-12PB-LE21

Housing for Male Terminals, Wire-to-Wire, 12 Position, .359 in [9.12 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal,

Panel Mount

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > DEUTSCH DT Series Housings & Connectors











Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 1.59 mm [ .063 in ]

Connector System: Wire-to-Wire

Number of Positions: 12

Centerline (Pitch): 9.12 mm [ .359 in ]

All DEUTSCH DT Series Housings & Connectors (461)

#### **Features**

### **Product Type Features**

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable

#### **Configuration Features**

Blank Cavity Position	0
Connector Modification	Sealed Flange, End Cap, One Piece Design
Connector Seal Code	E Seal
Number of Positions	12
Number of Rows	2



Electrical Characteristics	
Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V
Body Features	
Cable Exit Angle	180°
Body Material	PA GF
Primary Product Color	Black
Connector Code	В
Contact Features	
Contact Size	Size 16
Contact Type	Pin
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
Mounting Feature	With
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	9.12 mm[.359 in]
Dimensions	
Product Width	88.34 mm[3.478 in]
Product Length	52.37 mm[2.062 in]
Product Height	44.07 mm[1.735 in]
Row-to-Row Spacing	4.45 mm[.175 in]
Accepts Wire Insulation Diameter Range	1.35 – 3.05 mm[.053 – .12 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]



#### Operation/Application

Circuit Application	Power & Signal
Industry Standards	
Agency/Standard	SAE J2030
Degree of Protection	IP68, IP6K9K
UL Flammability Rating	12mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	100
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# Compatible Parts











TE Part # CAT-D487-CH8172
DEUTSCH DT Series Housings &
Connectors



TE Part # DT-RT1
EXT TOOL, FRONT RELEASE



TE Part # CAT-D487-P729
DEUTSCH DT DUST CAPS





TE Part # CAT-D48-SFT273

DEUTSCH STAMPED & FORMED

CONTACTS



TE Part # DT12P-BT-BK BOOT, 12P, REC, ST, BLK



TE Part # DT12P-BT BOOT, 12P, REC, ST, GRY




TE Part # DT12P-BT-EN BOOT, 12P, REC, ST, LONG, GRY



### Also in the Series | DEUTSCH DT



Automotive Connector Caps & Covers (98)



Automotive Connector Locks & Position Assurance(73)



Automotive Housings(619)



Automotive Seals & Cavity Plugs(4)





Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(14)



PCB Headers & Receptacles(106)

## Customers Also Bought



TE Part #36203 TERMINAL, PIDG R 16-14HD 1/2

















TE Part #DT04-12PA-KIT DT04-12PA AND WEG ONLY

### **Documents**

**Product Drawings** 

REC, 12P, BLK, E, FLANGE, B

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DT04-12PB-LE21\_99\_c-dt04-12pb-le21-99.2d\_dxf.zip

Housing for Male Terminals, Wire-to-Wire, 12 Position, .359 in [9.12 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal, Panel Mount



English

**Customer View Model** 

ENG\_CVM\_CVM\_DT04-12PB-LE21\_99\_c-dt04-12pb-le21-99.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DT04-12PB-LE21\_99\_c-dt04-12pb-le21-99.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

**CONNECTOR SELECTOR** 

English

**Product Specifications** 

**Application Specification** 

English

**Agency Approvals** 

**UL Report** 

English