

A. System Overview



Flanged Fork Terminals, Nylon Insulated – Funnel Entry

B1. Cable Ties

Type PNF-FF


- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Flange design provides extra secure connection on a variety of applications
- Fork design provides for fast and easy installation, without the need to remove fastener

- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B

B2. Cable Accessories

B3. Stainless Steel Ties

C1. Wiring Duct



C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

| Part Number | Wire Range | Color Code | Stock Thickness (In.) | Max. Ins. (In.) | Stud Size | Figure Dimensions (In.) | | | CA9 Series Crimp Die | CA-800/EZ Series Crimp Die | Pieces Per Reel |
|---------------------|-------------|------------|-----------------------|-----------------|-----------|-------------------------|------|------|----------------------|----------------------------|-----------------|
| | | | | | | L | W | C | | | |
| PNF18-6FF-3K | 22 – 18 AWG | Red | 0.03 | 0.145 | #6 | 0.80 | 0.28 | 0.19 | CD9-1A | CD-800-1 | 3000 |
| PNF18-8FF-3K | | | | | #8 | 0.87 | 0.31 | 0.23 | | | 3000 |
| PNF18-10FF-3K | | | | | #10 | 0.86 | 0.35 | 0.23 | | | 3000 |
| PNF14-6FF-3K | 16 – 14 AWG | Blue | 0.03 | 0.162 | #6 | 0.80 | 0.28 | 0.19 | CD9-2A | CD-800-2 | 3000 |
| PNF14-8FF-3K | | | | | #8 | 0.87 | 0.31 | 0.23 | | | 3000 |
| PNF14-10FF-3K | | | | | #10 | 0.87 | 0.35 | 0.23 | | | 3000 |
| PNF10-8FF-2K | 12 – 10 AWG | Yellow | 0.04 | 0.225 | #8 | 1.05 | 0.38 | 0.24 | CD9-3B | CD-800-3 | 2000 |
| PNF10-10FF-2K | | | | | #10 | 1.05 | 0.38 | 0.24 | | | 2000 |

For applicator information, see page D1.143.

D1. Terminals



Flanged Fork Terminals, Vinyl Insulated – Funnel Entry

D2. Power Connectors

Type PV-FFB


- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Flange design provides extra secure connection on a variety of applications
- Fork design provides for fast and easy installation, without the need to remove fastener

- Insulation support helps to prevent wire damage in bending applications
- UL Flammability UL 94V-0, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B

D3. Grounding Connectors

E1. Labeling Systems

E2. Labels



E3. Pre-Printed & Write-On Markers

E4. Permanent Identification

E5. Lockout/Tagout & Safety Solutions

| Part Number | Wire Range | Color Code | Stock Thickness (In.) | Max. Ins. (In.) | Stud Size | Figure Dimensions (In.) | | | CA9 Series Crimp Die | CA-800/EZ Series Crimp Die | Pieces Per Reel |
|----------------------|-------------|------------|-----------------------|-----------------|-----------|-------------------------|------|------|----------------------|----------------------------|-----------------|
| | | | | | | L | W | C | | | |
| PV18-6FFB-3K | 22 – 18 AWG | Red | 0.03 | 0.150 | #6 | 0.80 | 0.28 | 0.19 | CD9-1A | CD-800-1 | 3000 |
| PV18-8FFB-3K | | | | | #8 | 0.87 | 0.31 | 0.23 | | | 3000 |
| PV18-10FFB-3K | | | | | #10 | 0.86 | 0.35 | 0.23 | | | 3000 |
| PV14-6FFB-3K | 16 – 14 AWG | Blue | 0.03 | 0.170 | #6 | 0.80 | 0.28 | 0.19 | CD9-2A | CD-800-2 | 3000 |
| PV14-8FFB-3K | | | | | #8 | 0.86 | 0.31 | 0.23 | | | 3000 |
| PV14-10FFB-3K | | | | | #10 | 0.86 | 0.35 | 0.23 | | | 3000 |
| PV10-8FFB-2K | 12 – 10 AWG | Yellow | 0.04 | 0.225 | #8 | 1.03 | 0.37 | 0.22 | CD9-3B | CD-800-3 | 2000 |
| PV10-10FFB-2K | | | | | #10 | 1.03 | 0.37 | 0.22 | | | 2000 |

For applicator information, see page D1.143.

F. Index