

**Direct Link**

- [Cross reference](#)
- [RoHS/LF P/N Search](#)
- [Customer drawing search](#)
- [3D model search](#)
- [Application tooling](#)

**Services**

- [Contact us](#)
- [Distributor list](#)
- [Price request](#)
- [Order samples](#)


**Documentation**

- [Free search](#)
- [Search by category](#)

Start > Search=SICFHPE04BK\* > SICFHPE04BK

SICFHPE04BK

**SICFHPE04BK : 4 Way 1.5 Female mini seal housing**



Assistant Add to Favorites

Email Datasheet Print Datasheet

FCI Brings You More

Contact our sales/technical support

Sample request

Price request

Customer Drawing

**Specifications**

General	Mechanical	Physical	Terminal 1 Type	Environmental	Other Features
<b>General</b>					
Application	Engine Compartment Connectors Component to Wire				
Ways	4				
Coding version	Black				
Product Type	Housing				
Coding	Yes				
Features	Terminal Position Assurance (T.P.A.) Go - No - Go Housing Locking Principle Reduced Size Sealed Housing Acceptable Wire Size Range from 0.5 to 2 mm <sup>2</sup> Rear Sealing Ensured by a Pre - Mounted Mat - Seal				
Hybrid	No				
Main Terminal family	SICMA				
Main Terminal size	1.5 mm				
Sealed	Yes				
Terminal Size	1.5				
<b>Mechanical</b>					
Connector mating force	< 60 N				
<b>Physical</b>					
Color	Black				
Material	PBT				
Temperature (Range)	-40°C to +125°C				
<b>Terminal 1 Type</b>					
Terminal type 1	SICMA Female 1.5 mm Terminal				
Ways for Terminal Type 1	4				
Contact insertion force for Terminal Type 1	< 10 N				
Contact Pitch for Terminal Type 1	3.33 mm				
Retention force (Contact) for Terminal Type 1	> 60N				
<b>Environmental</b>					
IMDS	Yes				
<b>Other Features</b>					
Market	Passenger Vehicles				
Type	Female				
Part Situation	Active				
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.				