





SECTION A-A



GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.20	±0.25	±0.30	±30'	0.10	

NOTE

- 제품기능상 유해한 BURR, 변형 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL: ST730623, 624, 625
- 적용 HOUSING: MG51359
- SPACER는 본 도면과 같이 1차 LOCK'G 상태로 유지, 공급할 것.

NO.	MATERIAL	COLOR
0	P B T:	NATURAL
1		RED
2		BLUE
3		YELLOW
4		GRAY
5		BLACK
6		W/GREEN
7		BROWN
8		GREEN



ISSUE MARK

NO.	PART NO.	PART NAME	MATERIAL	FINISH
1	MG671360	.090 II W/P 3P REC. HOUSING	SEE TABLE	GRAY
2	MG671361	.090 II W/P 3P REC. FRONT HOLDER	SILICONE	NATURAL
3	P900704	.090 II W/P 3P INNER SEAL	SILICONE	BLACK

						MATERIAL		SEE TABLE	 KET KOREA ELECTRIC TERMINAL CO., LTD.
						FINISH		SEE TABLE	
						WIRE RANGE			
						INSULATION			
								CLASS	.090 II SEALED
								TYPE	7283-7031
LTR	REVISION RECORD		DR	CHK	APP	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.
							SEE TABLE	2/1	MG641362
DR.	WON. '97.07.15		CHK	9/7	4/15	PART NAME			
CHK.	CHW		APP	4/15	.090 II W/P 3P REC. ASS'Y				